SONALIKA



50 RX

















STEERING Steering

ELECTRICAL Battery

Alternator

Stay Bars

Lift rods

HYDRAULICS 3 point linkage

Seven pin trailer socket

Hydraulic lifting capacity

Auxiliary hydraulic circuit

Manual

12V, 88 12V, 36Ah

Standard

Swinging Drawbar

CAT-II

1600 kg

Standard

2DA





FEATURES		FEATURES	
Model Description	Sonalika-50		
ENGINE		SAFETY SWITCH	
Engine Type	Three Cylinder Natural Aspirated Engine	Clutch Safety Switch	Standard
HP Category	50	PTO Safety Switch	Standard
No. of Cylinders	3	Neutral Safety Switch	Standard
Aspiration	Natural	CAPACITY (LTRS)(+/-5%)	
Cubic Capacity (cc)	2893	Fuel tank (Lit)	55
Rated RPM (+/-25mm)	2100	TYRE	
Air cleaner	Dry Type	Front	6-16
Cold Start	Yes	Rear	13.6-28
Max Torque (Nm)	190@1200 RPM	DIMENSION & WEIGHT(+/-5%)	
Exhaust	Upward	Weight(kg)	2740
TRANSMISSION		Wheel Base (mm)	2075
Drive	2WD	Total Length (mm)	3646
Clutch	Dual Clutch	Total Width (mm)	1879
Gearbox	8F+2R	Height (mm) Up to ROPS	2461
Front Axle	2WD	Min Ground Clearance (mm)	293
Transmission	Constant Mesh	Front Track (mm)	1370
SPEED (FORWARD)		Rear Track (mm)	1423
Maximum Speed (Km/Hr)	29.94@2100	OTHERS	
Minimum Speed (Km/Hr)	2.42@2100	Fuel Indicator gauge	Standard
BRAKES		Front Toe Hook	Standard , inbuilt in front weight
Brakes	Oil Immersed Brake	Front & rear weights with std. Ballast	Base Weight 72Kg+Front 6X29 Kg and Rear 2X34 Kg on each wheel.
Type of actuation	Mechanical	Trailer Hitch	Swinging Drawbar
Parking Brake	Independent Type	ROPS	Standard
DIFFERENTIAL LOCK		OPTIONAL FEATURES	Standard
Differential lock	Independent Mechanical	Tyres (Radial Tyre)	Rear 14.928
РТО			
PTO (rpm)	540@1680ERPM	prior notice. E&OE, Please correlate with latest updates, a	cification and details provided are subject to change without coessories shown may not be part of standres product.
PTO (actuation)	Mechanical		

DEALER STAMP

INTERNATIONAL TRACTORS LIMITED