## SONALIKA



60 RX





















FEATURES	
Model Description	Sonalika-60
ENGINE	
Engine Type	Three Cylinder Natural Aspirated Engine
HP Category	60
No. of Cylinders	3
Aspiration	Turbo
Cubic Capacity (cc)	2780
Rated RPM (+/-25mm)	2100
Air cleaner	Dry Type
Cold Start	Standard
Max Torque (Nm)	230(+-5%)
Exhaust	Underhood Upward
TRANSMISSION	
Drive	2WD
Clutch	Dual Clutch
Gearbox	8F+2R
Front Axle	2WD
Transmission	Constant Mesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	32.05
Minimum Speed (Km/Hr)	2.45
BRAKES	
Brakes	Oil Immersed Brake
Type of actuation	Mechanical
Parking Brake	Independent Type
DIFFERENTIAL LOCK	
Differential lock	Standard
РТО	
PTO (rpm)	540@1680ERPM
STEERING	
Steering	Power
ELECTRICAL	
Battery	12V, 88 / 110 Ah
Alternator	12V, 36Ah
Seven pin trailer socket	Standard
HYDRAULICS	
3 point linkage	CAT-II
Stay Bars	Swinging Drawbar
Hydraulic lifting capacity	2000 kg
Auxiliary hydraulic circuit	2DA
Lift rods	Standard

FEATURES	
SAFETY SWITCH	
Clutch Safety Switch	Standard
PTO Safety Switch	Standard
Neutral Safety Switch	Standard
CAPACITY (LTRS)(+/-5%)	
Fuel tank (Lit)	65
TYRE	
Front	7.5-16
Rear	13.6-28
DIMENSION & WEIGHT(+/-5%)	
Weight(kg)	2740
Wheel Base (mm)	2075
Total Length (mm)	3910
Total Width (mm)	1875
Height (mm) Up to ROPS	2650
Min Ground Clearance (mm)	365
Front Track (mm)	1370
Rear Track (mm)	1423
OTHERS	
Fuel Indicator gauge	Standard
Front Toe Hook	Standard, inbuilt in front weight
Front & rear weights with std. Ballast	Base Weight 72Kg+Front 6X29 Kg and
	Rear 2X34 Kg on each wheel.
Trailer Hitch	Swinging Drawbar
ROPS	Standard
OPTIONAL FEATURES	
Tyres	Rear 14.9-28

\*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, Please correlate with latest updates, accessories shown may not be part of standres product.

**DEALER STAMP** 

(Tanzania